



SAFETY DATA SHEET

GRIPDECK WEARCOAT RESIN (all colours)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name GRIPDECK WEARCOAT RESIN (all colours)
Product number B3654-B3657
Internal identification GRIPDECKWR/9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Component of Car Park Decking Repair System
Uses advised against None

1.3. Details of the supplier of the safety data sheet

Supplier

Don Construction Products Ltd.,
Hawthorn House
Helions Bumpstead Road
Haverhill
Suffolk
CB9 7AA
Tel: 01538 361799 Mon-Fri 08:30 - 17:00 (excl bank holidays)
Fax: 01538 361899
E-Mail: info.uk@dcp-int.com

1.4. Emergency telephone number

Emergency telephone 01538 361799 Mon-Fri 8.30am - 5.00pm (excluding Bank Holidays)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified
Health hazards Not Classified
Environmental hazards Not Classified

2.2. Label elements

Hazard statements NC Not Classified

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Composition comments Polyalcohol with ester and ether groups containing additives.

SECTION 4: First aid measures

4.1. Description of first aid measures

GRIPDECK WEARCOAT RESIN (all colours)

General information	Remove affected person from source of contamination.
Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. Get medical attention if any discomfort continues.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	No specific symptoms known.
Ingestion	No specific symptoms known.
Skin contact	Prolonged skin contact may cause redness and irritation.
Eye contact	May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with the following media: Small fires: Foam, carbon dioxide or dry powder. Larger fires: Water spray.
-------------------------------------	--

5.2. Special hazards arising from the substance or mixture

Specific hazards	No unusual fire or explosion hazards noted.
Hazardous combustion products	Does not decompose when used and stored as recommended.

5.3. Advice for firefighters

Protective actions during firefighting	No specific firefighting precautions known.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate.
-----------------------------	--

6.2. Environmental precautions

Environmental precautions	Avoid the spillage or runoff entering drains, sewers or watercourses.
----------------------------------	---

6.3. Methods and material for containment and cleaning up

GRIPDECK WEARCOAT RESIN (all colours)

Methods for cleaning up

Small Spillages: Absorb spillage with sand or other inert absorbent. Large Spillages: Contain and absorb spillage with sand, earth or other non-combustible material. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Collect spillage in steel containers, seal securely and deliver for disposal according to local regulations.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Provide adequate ventilation. Good personal hygiene procedures should be implemented. Do not eat, drink or smoke when using the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep separate from food, feedstuffs, fertilisers and other sensitive material. Store in tightly-closed, original container in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

CYCLOHEXANONE

Long-term exposure limit (8-hour TWA): WEL 10 ppm 41 mg/m³

Short-term exposure limit (15-minute): WEL 20 ppm 82 mg/m³

Sk

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation.

Personal protection

Always check applicability with your supplier of protective equipment.

Eye/face protection

If there is a risk of splashing, wear chemical resistant goggles or visor approved to BS EN166.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Nitrile gloves to BSEN374 are recommended. Break through times can vary depending on thickness, use and source. Change gloves regularly.

Other skin and body protection

Wear suitable protective clothing as protection against splashing or contamination. Wear apron or protective clothing in case of contact.

GRIPDECK WEARCOAT RESIN (all colours)

Hygiene measures	Provide eyewash station. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated. Wash contaminated clothing before reuse.
Respiratory protection	No specific recommendations.
Environmental exposure controls	Keep container tightly sealed when not in use.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Various colours.
Odour	Almost odourless.
Odour threshold	Not determined.
pH	Not applicable.
Melting point	Not applicable.
Initial boiling point and range	Not determined.
Flash point	>100°C
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Not applicable.
Other flammability	Not applicable.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	1.6 approx @ 20°C
Bulk density	Not determined.
Solubility(ies)	Immiscible with water.
Partition coefficient	Not determined.
Auto-ignition temperature	Not applicable.
Decomposition Temperature	Not determined.
Viscosity	8500 mPa s @ 20°C
Explosive properties	Not applicable.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	Not determined.
Comments	Information given is applicable to the product in its ready-to-use form.

9.2. Other information

GRIPDECK WEARCOAT RESIN (all colours)

Other information	None.
Refractive index	Not determined.
Particle size	Not applicable.
Molecular weight	Not determined.
Volatility	Not determined.
Saturation concentration	Not applicable.
Critical temperature	Not determined.
Volatile organic compound	Not determined.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
-----------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
------------------------------------	---

10.4. Conditions to avoid

Conditions to avoid	Avoid exposure to high temperatures or direct sunlight.
---------------------	---

10.5. Incompatible materials

Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
--------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Does not decompose when used and stored as recommended.
----------------------------------	---

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects	No information available.
<u>Acute toxicity - oral</u>	
Notes (oral LD ₅₀)	No specific test data are available.
<u>Acute toxicity - dermal</u>	
Notes (dermal LD ₅₀)	No specific test data are available.
<u>Acute toxicity - inhalation</u>	
Notes (inhalation LC ₅₀)	No specific test data are available.
<u>Skin corrosion/irritation</u>	
Skin corrosion/irritation	Not irritating.
Animal data	No specific test data are available.
Human skin model test	No specific test data are available.
Extreme pH	No specific test data are available.

GRIPDECK WEARCOAT RESIN (all colours)

Serious eye damage/irritation

Serious eye damage/irritation Not irritating.

Respiratory sensitisation

Respiratory sensitisation Not sensitising.

Skin sensitisation

Skin sensitisation Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Does not contain any substances known to be mutagenic.

Genotoxicity - in vivo Does not contain any substances known to be mutagenic.

Carcinogenicity

Carcinogenicity Does not contain any substances known to be carcinogenic.

IARC carcinogenicity Not listed.

Reproductive toxicity

Reproductive toxicity - fertility Does not contain any substances known to be toxic to reproduction.

Reproductive toxicity - development Does not contain any substances known to be toxic to reproduction.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Not relevant.

General information No specific health hazards known.

Inhalation May cause some discomfort in poorly ventilated areas.

Ingestion May cause discomfort if swallowed.

Skin contact Prolonged or repeated exposure may cause some irritation of the skin.

Eye contact May cause temporary eye irritation.

Acute and chronic health hazards No specific health hazards known.

Target organs No specific target organs known.

Medical symptoms No specific symptoms noted.

Medical considerations No information available.

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT; KEROSENE - UNSPECIFIED

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >5 000 mg/kg, , Rat

CYCLOHEXANONE

Acute toxicity - oral

GRIPDECK WEARCOAT RESIN (all colours)

ATE oral (mg/kg)	500.0
<u>Acute toxicity - dermal</u>	
ATE dermal (mg/kg)	1,100.0
<u>Acute toxicity - inhalation</u>	
ATE inhalation (vapours mg/l)	11.0

SECTION 12: Ecological Information

Ecotoxicity The product should not be allowed to enter drains, sewers or watercourses.

12.1. Toxicity

Toxicity Not measured. Do not allow to enter waterways or drains

Acute toxicity - fish Not determined

Acute toxicity - aquatic invertebrates Not determined.

Acute toxicity - aquatic plants Not determined.

Acute toxicity - microorganisms Not determined.

Acute toxicity - terrestrial Not determined.

Chronic toxicity - fish early life stage Not determined.

Short term toxicity - embryo and sac fry stages Not determined.

Chronic toxicity - aquatic invertebrates Not determined.

12.2. Persistence and degradability

Persistence and degradability The product is not readily biodegradable. Fully cured product, following use, is resistant to degradation but is inert and unlikely to cause ecological effects.

Phototransformation Not determined.

Stability (hydrolysis) Not determined.

Biodegradation Not determined.

Biological oxygen demand No specific test data are available.

Chemical oxygen demand No specific test data are available.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

12.4. Mobility in soil

Mobility The product is non-volatile.

Adsorption/desorption coefficient Not determined.

GRIPDECK WEARCOAT RESIN (all colours)

Henry's law constant Not determined.

Surface tension Not determined.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Small quantities of product may be treated with an equivalent quantity of product hardener, allowed to cure and disposed of as low hazard waste. Larger quantities should be disposed of as controlled liquid waste via a licensed waste operator.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

Transport labels

No transport warning sign required.

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Control of Substances Hazardous to Health Regulations 2002 (as amended).

Guidance Workplace Exposure Limits EH40.
Safety Data Sheets for Substances and Preparations.

Authorisations (Title VII Regulation 1907/2006) No specific authorisations are known for this product.

Restrictions (Title VIII Regulation 1907/2006) No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information Don Construction Products Ltd. Technical Datasheet.

GRIPDECK WEARCOAT RESIN (all colours)

Key literature references and sources for data	Health and Safety Executive Guidance Note EH40 (amended annually). Workplace Exposure Limits.
Revision comments	Section 1 update
Revision date	01/03/2017
Revision	9
Supersedes date	25/05/2016
SDS status	Approved.
Risk phrases in full	Not classified. R10 Flammable. R20 Harmful by inhalation. R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.